

## Fiberglass Pipe, Duct & Fittings




**FRP Filament Wound Pipe**



**FRP Hand Lay-Up Pipe**

All FRP (Piping Systems) are custom fabricated to order based on chemical service, pressure/vacuum and mechanical conditions.



### FRP Product Features

- Manufactured to conform to PS 15-69, ASTM D5421 and CGSB-41-GP-22.
- Nexus and C-Veil + 2 mat Corrosion Liner.
- Hand lay up and filament wound
- Available in size range 2 to 60 inch.
- Pipe Flanges are spot-faced and coated with resin, to 150 lb drilling pattern.
- Resins available in DOW DERAKANE "MOMENTUM", 411-350 and 470, Hetron 922, Swancor 901. Hetron 992 FR, Derakane 441 and Derakane 411 BPO-DMA cure.
- Pre-spooling available on request.

## GVS-65 Gas Venting System



The GVS-65 is a complete PVC pipe system designed for use as BH, Class II gas vent with a maximum operating temperature of 65oC. The GVS-65 gas appliance system has been third party certified ULC S636-95. This system included pipe, fittings, solvent cement and primer. Only GVS-65 components may be used as part of the system. Do not use fittings, pipe, solvent cement or primer from any other manufacturer with the GVS-65 Gas Venting System.



| PRODUCT      | PRODUCT DESCRIPTION                           | CASE QTY |
|--------------|---|----------|
| GVS65010211  | 1-1/2" PVC GAS VENT PIPE 10 FT LENGTHS GVS-65 | 1510     |
| GVS65010212  | 2" PVC GAS VENT PIPE 10 FT LENGTHS GVS65      | 1050     |
| GVS65010213  | 2-1/2" PVC GAS VENT PIPE 10 FT LENGTHS GVS65  | 780      |
| GVS65010214  | 3" PVC GAS VENT PIPE 10 FT LENGTHS GVS65      | 580      |
| GVS65010216  | 4" PVC GAS VENT PIPE 10 FT LENGTHS GVS65      | 510      |
| GVS650706200 | PVC GAS VENT SOLVENT CEMENT 950 ML QUART      | 12       |
| GVS650706300 | PVC GAS VENT SOLVENT CEMENT 475 ML PINT       | 12       |
| GVS650707200 | PVC & CPVC GAS VENT PRIMER 950 ML QUART       | 12       |
| GVS650707300 | PVC & CPVC GAS VENT PRIMER 475 ML PINT        | 12       |
| GVS650708200 | PVC/ABS GAS VENT TRANSITION CEMENT 950 ML QTS | 12       |
| GVS650708300 | PVC/ABS GAS VENT TRANSITION CEMENT 475 ML PNT | 12       |
| GVS65401020  | 2" PVC GAS VENT TEE GVS65                     | 35       |
| GVS65406020  | 2" X 90 DEG PVC GAS VENT ELBOW GVS65          | 50       |
| GVS65406020L | 2" X 90 DEG PVC GAS VENT ELBOW LONG RAD GVS65 | 55       |
| GVS65406030  | 3" X 90 DEG PVC GAS VENT ELBOW GVS65          | 25       |
| GVS65406030L | 3" X 90 DEG PVC GAS VENT ELBOW LONG RAD GVS65 | 23       |
| GVS65406040  | 4" X 90 DEG PVC GAS VENT ELBOW GVS65          | 20       |
| GVS65417020  | 2" X 45 DEG PVC GAS VENT ELBOW GVS65          | 110      |
| GVS65417030  | 3" X 45 DEG PVC GAS VENT ELBOW GVS65          | 25       |
| GVS65417040  | 4" X 45 DEG PVC GAS VENT ELBOW GVS65          | 20       |
| GVS65429015  | 1-1/2" PVC GAS VENT COUPLING GVS65            | 25       |
| GVS65429020  | 2" PVC GAS VENT COUPLING GVS65                | 70       |
| GVS65429025  | 2-1/2" PVC GAS VENT COUPLING GVS65            | 20       |
| GVS65429030  | 3" PVC GAS VENT COUPLING GVS65                | 60       |
| GVS65429040  | 4" PVC GAS VENT COUPLING GVS65                | 30       |
| GVS65429338  | 3" X 2" PVC GAS VENT INCREASER GVS65          | 45       |
| GVS65429422  | 4" X 3" PVC GAS VENT INCREASER GVS65          | 30       |
| GVS65437251  | 2" X 1-1/2" PVC GAS VENT RED BUSHING GVS65    | 80       |
| GVS65437339  | 3" X 2-1/2" PVC GAS VENT RED BUSHING GVS65    | 20       |
| GVS65VS020   | 2" GAS VENT TERMINATION VENT SCREEN           | 250      |
| GVS65VS030   | 3" GAS VENT TERMINATION VENT SCREEN           | 100      |

Note: Also available in CPVC for flue gas temperatures of up to 90°C

### Features

- Certified under ULC S636-95
- Complete system includes pipe, fittings, cement and primer
- Available from 1 1/2" to 4" diameter
- All pipe, fittings and cement are labeled as certified

### Applications

- Furnaces
- Fireplaces
- Boilers
- Water Heaters